

REGISTERED OFFICE 2C RAMANIYAM SAMPOORNA, 73 LB ROAD, THIRUVANMIYUR, CHENNAI - 600041

HEAD OFFICE 70 Sathya Nagar II Cross, Padi, Chennai - 600050

91 044 26253705 / 91 9884069859 U74990TN2019PTC128177 CIN

PAN AAFCE4210J TAN CHEE07878D GSTIN 33AAFCE4210J1Z1



PRODUCT DATA SHEET - ECZ G D475



Garbodrain 4750

| Product description | Garbodrain -Food waste disposer |
|--------------------------|--|
| Model No. | G4750 |
| iviouei ivo. | DESIGN |
| 7 20.00 | |
| Model Type | Heavy duty Stand-alone machine with self-contained with Large sink |
| Mounting Type | Floor standing independent unit |
| Feeding Type | Continuous feed |
| Crushing Type | By Centrifugal force with the help of 7.5hp 3 phase induction motor |
| Disposal type | Instant crushing & disposal on line |
| DESCRIPTION & MATERIAL | |
| Crusher Housing 8" | Steel Casting embedded with specially designed SS 304 serrated ring at |
| | grinding area With High speed uniquely designed sturdy rotating disc |
| | assembly & sieve in SS 304 running on 2 Ball bearings with special sealing |
| | arrangement |
| Topcover | Material holding cover in Casting bolted to Crusher housing |
| Body | Stand Alone unit with sink made in SS 304 mounted on 4 Anti vibro mounts |
| Out Let | 2" GI nipple |
| TECHNICAL SPECIFICATIONS | |
| Over all machine Size | 1050mm x 685mm x 850mm (LxBxH) |
| Inlet | 150mm |
| Out let size & Position | 2" nipple at the bottom directed downwards |
| Machine weight | 170kg |
| Motor | 7.5hp / 1440rpm / 3Phase Induction Motor / Continuous duty |
| | Drives crusher assembly through V Belt |
| Electricals | 3m long 4 core cable Ready to connect to a Three phase 7.5hp starter |
| Drain Hole | 2" |
| Capacity | 800kg per hour by Continuous feed with 4 Litre holding capacity |
| Installation | 3/4" water Tap at 950mm height / 3phase line with Starter suitable for 7.5hp |
| requirements | (10-20A range / 2" Drain connection |